

## High Speed Swing Boom



- The unit is an ideal for:
- Cutting on uneven terrain
  - Cutting on delicate vegetation
  - Clearing out fence rows.
  - Brush removal

Price: \$12,850.00 msrp

The Turbo Saw Swing Boom allows the operator to stop the skid steer and use the boom to maneuver the cutting disc from side to side in a 10' foot arch well outside the wheelbase on both side of the skid steer. This feature greatly increases operator precision and decreases the maneuvering required of the skid steer thereby minimizing damage done to the ground. A wiring harness and waterproof buttons are included to operate the swing boom feature (an 8 pin or 14 pin external plug is available). This attachment comes in either standard flow or high flow models.

### INCLUDED ITEMS

#### Safety Features:

- Hydraulic Hose Sleeves
- Blade Shield •Pushing Guard
- V deflector with metal deflector shield
- Built-in 5 gallon sprayer tank/ pump

#### Standard Features:

- Hoses
- Hydraulic couplers
- Hardened skid plate

#### Frame Design:

- Lifetime frame warranty

#### Cutting Tooth:

- Carbide bolt-on cutting tooth.
- Below ground cutting durability.
- In-field replacement if necessary.
- Small bite (1/8") equals safer operation

#### Drivetrain:

- No maintenance or adjustment on the drive train for up to 800 to 1200 hours.



		Specifications:				
Model:	Hydraulic Requirements:	Length:	Height:	Weight:	Blade Diameter:	Cutting Speed:
SB2600	15-23 gpm.	6' 11"	59"	1,050lbs.	30"	3-6" per second.
SB3000	24-41 gpm.	6' 11"	59"	1,050lbs.	30"	6-10" per second.