

# Rotating/ Swing/ Grind Saws

RS2600, RS3000, RS3400



**RS2600**



**RS3000**



**RS3400**

Model	RS2600	RS3000	RS3400
-------	--------	--------	--------

## CUTTING CAPACITY:

Cutting Capacity	30"	30"	34"
Cutting Depth	11.25"	11.25"	13.25"
Cutting Speed Per Sec.	3-6"	6-10"	6-10"

Can grind 12+” below ground

## SWING CAPABILITY:

8’ Swing

## SKID LOADER COMPATIBILITY:

HP Requirements	60+	70+	80+
Hydraulic Flow Required	15-23 gpm	24-42 gpm	24-42 gpm
Case Drain Required	No	Yes	Yes
Mounting Type	Universal Quick Attach		

## DIMENSIONS:

Length	84"	84"	88"
Width	46"	46"	46"
Height	48"	48"	48"
Weight	975 lb	975 lb	1,100 lb

## CUTTING DISC:

Width	30"	30"	34"
Thickness	1/2"	1/2"	1/2"
Carbide Teeth	15	15	16
Kerf (cutting width)	1"	1"	1"
Tooth Bite	1/8"	1/8"	1/8"
Cutting Disc RPM	1,800-2,000	1,800-2,000	1,800-2,000

## SHIELDING:

150° Shielding

## INCLUDED ADDITIONAL FEATURES:

Sprayer System (5 Gallon Tank & Herbicide / Diesel Capable Pump)  
Multi-Surface Blade



© Dougherty Forestry Mfg. Ltd, Co.  
211 W. Canyon Run, Hinton, OK 73047  
Phone: (405) 542-3520